



Utility PVC Ball Valves



Primary Application

A high quality, economical, quarter-turn shutoff valve designed for home irrigation, pool and spa applications. Available in IPS sizes

1/2" thru 2" with a choice of either socket or threaded end connections.

Features:

- One piece sealed unit never requires adjustment
- Heavy bodied PVC construction
- Standard EPDM O-rings
- High impact Polypropylene handle with double stop engagement
- Equipped with Spears high strength Safe-T-Shear stem
- All Utility Ball Valves are NSF listed for potable water use

ITEM	DESCRIPTION
20001810	1/2 SPEARS UTILITY SS BV
20001820	3/4 SPEARS UTILITY SS BV
20001830	1 SPEARS UTILITY SS BV
20001840	1-1/4 SPEARS UTILITY SS BV
20001850	1-1/2 SPEARS UTILITY SS BV
20001860	2 SPEARS UTILITY SS BV
20001870	2-1/2 SPEARS UTILITY SS BV
20001880	3 SPEARS UTILITY SS BV
20001890	4 SPEARS UTILITY SS BV
20001910	1/2 SPEARS UTILITY TT BV
20001920	3/4 SPEARS UTILITY TT BV
20001930	1 SPEARS UTILITY TT BV
20001940	1-1/4 SPEARS UTILITY TT BV
20001950	1-1/2 SPEARS UTILITY TT BV
20001960	2 SPEARS UTILITY TT BV

Jandy 2 & 3 Port Valves



Primary Application

Jandy Port Valves never need lubricating and they are guaranteed never to fail. Made from sturdy CPVC, the valve

is very resistant to temperature and chemical fluctuations.

ITEM	DESCRIPTION
20003250	1 1/2 IN 3-PORT NEVRLUB VL JANDY
20003270	2 1/2 IN 3-PORT NEVRLUB VL JANDY
20003350	1 1/2 IN 2-PORT NEVRLUB VL JANDY
20003370	2 1/2 IN 2-PORT NEVRLUB VL JANDY



Slip PVC Knife Gate Valves

ITEM	DESCRIPTION
20004050	1-1/2 SLIP PVC KNIFE GATE VALVE
20004060	2IN SLIP PVC KNIFE GATE VALVE
20004080	3IN SLIP PVC KNIFE GATE VALVE

Drinking Fountain Valve

Features:

- Self closing
- Solid brass with stainless steel ball bearing
- 1/2" NPT female thread



ITEM	DESCRIPTION
21000110	1/2 IN DRINKING FOUNTAIN VALVE



FBV/FBVS Full Port Ball Valves

- Pressure rated at 600 psi WOG and 400 psi WOG for 2 1/2" & 3" models
- Suitable for temperatures from 0° F to +350° F to 50 psi



ITEM	DESCRIPTION
21006410	1/2 FBV-3 FULL PORT THD BV
21006420	3/4 FBV-3 FULL PORT THD BV
21006430	1 FBV-3 FULL PORT THD BV
21006440	1-1/4 FBV-3 FULL PORT THD BV
21006450	1-1/2 FBV-3 FULL PORT THD BV
21006460	2 FBV-3 FULL PORT THD BV
21006470	2 1/2 FBV-3 FULL PORT THD BV
21006480	3 FBV-3 FULL PORT THD BV
21006510	1/2 FBVS-3 SWEAT FULL PORT BV
21006520	3/4 FBVS-3 SWEAT FULL PORT BV
21006530	1 FBVS-3 SWEAT FULL PORT BV
21006550	1-1/2 FBVS-3 SWT FULL PORT BV
21006560	2 FBVS-3 SWEAT FULL PORT BV
21006720	3/4 SWEAT BV W/DRAIN FULL PORT
21006730	1IN SWEAT BV W/DRAIN FULL PORT



Standard Port Ball Valve

Features:

- Rating: 600 PSI WOG, 150 PSI WSP
- 400° F maximum temperature

ITEM	DESCRIPTION
21006290	4 WBV WATTS STD PORT THD BV